



MS836

1D USB Laser Scanner

Light Source	Visible Laser Diode 650 nm
Scan Pattern	Single Scan
Skans Rate	100 scans/second
Scanning Width	22cm
Scan Angle	±30°
Decode Capability	EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 128, EAN128, Codabar, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, GS1, etc
Print Contrast	15% UPC/EAN 100%
Mention Pattern	Buzzer, Indicator
Scan Mode	Automatic
Size	95mm x 70mm x 160mm
Weight	150g
Material	ABS + PC

Cable	Standard 2M straight
Voltage	5VDC
Operating Current	85mA
Static Current	36mA
Operating Temperature	0°C to 45°C
Storage Temperature	-20°C to 60°C
Humidity	5% to 85% relative humidity, non-condensing
Drop Threshold	1.5M drops
IP Rating	IP42
Support Interface	USB 2.0
Cable Length	Standard 2.0M, Optional 2.8M
Warranty	30 days, 1 year or 2 years depending on contract
EMC	CE & FCC



Specifications subject to change without notice.

Copyright 2017 Unitech Electronics Co., Ltd.
All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd.

All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

unitech
unitechbarcode.com

Unitech America, Inc. | 6182 Katella Avenue | Cypress, CA 90630
714-891-6400 ph | 800-861-8648 toll | 714-891-5050 fx